



SAFETY DATA SHEET

Issue Date 09-Mar-2021

Revision Date 08-Apr-2021

Version %

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Nickel Low-Cobalt Alloy Powder

Other means of identification

Product Code PM032

Synonyms Nickel Low-Cobalt Alloy Powder, including but not limited to: ATI 625 PM™ Powder, ATI 625M PM™ Powder, ATI 718™ Powder, ATI 725 PM™ Powder, ATI HX™ Powder, Colmonoy 84 Powder, and MISC-N Powder

Recommended use of the chemical and restrictions on use

Recommended Use Alloy product manufacture.

Uses advised against

Details of the supplier of the safety data sheet

Manufacturer Address

ATI, 1000 Six PPG Place, Pittsburgh, PA
15222 USA

Emergency telephone number

Emergency Telephone Chemtrec: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Chronic aquatic toxicity	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction
May cause cancer
Suspected of causing genetic defects
May damage fertility or the unborn child
Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled
Harmful to aquatic life with long lasting effects

**Appearance** Powder**Physical state** Solid**Odor** Odorless**Precautionary Statements - Prevention**

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wear protective gloves

Avoid breathing dust/fume

In case of inadequate ventilation wear respiratory protection

Avoid release to the environment

IF ON SKIN: Wash with plenty of soap and water

Precautionary Statements - Response

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:

Titanium dioxide an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Nickel Low-Cobalt Alloy Powder, including but not limited to: ATI 625 PM™ Powder, ATI 625M PM™ Powder, ATI 718™ Powder, ATI 725 PM™ Powder, ATI HX™ Powder, Colmonoy 84 Powder, and MISC-N Powder.

Chemical Name	CAS No.	Weight-%
Nickel	7440-02-0	49 - <100
Titanium	7440-32-6	0 - 46
Chromium	7440-47-3	0 - 32
Iron	7439-89-6	0 - 21
Molybdenum	7439-98-7	0 - 10
Tungsten	7440-33-7	0 - 10
Niobium (Columbium)	7440-03-1	0 - 6
Aluminum	7429-90-5	0 - 5.5
Tantalum	7440-25-7	0 - 5
Silicon	7440-21-3	0 - 3
Cobalt	7440-48-4	0.1 - <2.5
Boron	7440-42-8	0 - 2
Carbon	7440-44-0	0 - 2
Hafnium	7440-58-6	0 - 1

4. FIRST AID MEASURES

First aid measures

Eye contact	In the case of particles coming in contact with eyes during processing, treat as with any foreign object.
Skin Contact	In the case of skin allergic reactions see a physician. Wash off immediately with soap and plenty of water.
Inhalation	If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove to fresh air and consult a qualified health professional. In the case of asthma symptoms or breathing difficulties call a physician:
Ingestion	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product. Isolate large fires and allow to burn out. Smother small fires with salt (NaCl).

Unsuitable extinguishing media Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with the burning material.

Specific hazards arising from the chemical

Intense heat. Very fine, high surface area material resulting from processing this product may ignite spontaneously at room temperature. WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

Hazardous combustion products Titanium dioxide an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Use personal protective equipment as required.
For emergency responders	Use personal protective equipment as required. Follow Emergency Response Guidebook, Guide No. 171, EXCEPT for FIRE follow Emergency Response Guidebook, Guide No. 170.

Environmental precautions

Environmental precautions Collect spillage to prevent release to the environment.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Sweep or shovel material into dry containers. Avoid creating uncontrolled dust.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PEL
Nickel 7440-02-0	TWA: 1.5 mg/m ³ inhalable fraction	TWA: 1 mg/m ³
Titanium 7440-32-6	-	-
Chromium 7440-47-3	TWA: 0.5 mg/m ³	TWA: 1 mg/m ³
Iron 7439-89-6	-	-
Tungsten 7440-33-7	STEL: 10 mg/m ³ STEL: 10 mg/m ³ W TWA: 5 mg/m ³ TWA: 5 mg/m ³ W	(vacated) STEL: 10 mg/m ³ (vacated) STEL: 10 mg/m ³ W
Molybdenum 7439-98-7	TWA: 10 mg/m ³ inhalable fraction TWA: 3 mg/m ³ respirable fraction	-
Niobium (Columbium) 7440-03-1	-	-
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction
Tantalum 7440-25-7	-	TWA: 5 mg/m ³
Silicon 7440-21-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction
Cobalt 7440-48-4	TWA: 0.02 mg/m ³ TWA: 0.02 mg/m ³ Co	TWA: 0.1 mg/m ³ dust and fume
Carbon 7440-44-0	-	-
Boron 7440-42-8	-	-
Hafnium 7440-58-6	TWA: 0.5 mg/m ³ TWA: 0.5 mg/m ³ Hf	TWA: 0.5 mg/m ³

Appropriate engineering controls

Engineering Controls Avoid generation of uncontrolled particles.

Individual protection measures, such as personal protective equipment

Eye/face protection	When airborne particles may be present, appropriate eye protection is recommended. For example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that shield the eyes from particles.
Skin and body protection	Fire/flame resistant/retardant clothing may be appropriate during hot work with the product. Wear protective gloves.
Respiratory protection	When particulates/fumes/gases are generated and if exposure limits are exceeded or irritation is experienced, proper approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Solid	Odor	Odorless
Appearance	Powder	Odor threshold	Not applicable
Color	Metallic gray or silver		
Property	Values	Remarks • Method	
pH	-	Not applicable	
Melting point / freezing point	1400-1540 °C / 2560-2800 °F		
Boiling point / boiling range	-		
Flash point	-		
Evaporation rate	-	Not applicable	
Flammability (solid, gas)	-	Product not flammable in the form as distributed, flammable as finely divided particles or pieces resulting from processing of this product	
Flammability Limit in Air			
Upper flammability limit:	-		
Lower flammability limit:	-		
Vapor pressure	-	Not applicable	
Vapor density	-	Not applicable	
Specific Gravity	8.0-8.5		
Water solubility	Insoluble		
Solubility in other solvents	-		
Partition coefficient	-	Not applicable	
Autoignition temperature	-	Not applicable	
Decomposition temperature	-	Not applicable	
Kinematic viscosity	-	Not applicable	
Dynamic viscosity	-	Not applicable	
Explosive properties	Not applicable		
Oxidizing properties	Not applicable		
Other Information			
Softening point	-		
Molecular weight	-		
VOC Content (%)	Not applicable		
Density	-		
Bulk density	-		

10. STABILITY AND REACTIVITY

Reactivity

Not applicable

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Dust formation and dust accumulation.

Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

Hazardous Decomposition Products

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated: Titanium dioxide an IARC Group 2B carcinogen. Hexavalent Chromium (Chromium VI) may cause lung, nasal, and/or sinus cancer. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

May cause cancer. Cobalt-containing alloys may cause sensitization by inhalation. Causes damage to the respiratory tract through prolonged or repeated exposure if inhaled.

Eye contact

Product not classified.

Skin Contact

May cause sensitization by skin contact.

Ingestion

Product not classified.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Nickel 7440-02-0	> 9000 mg/kg bw	-	> 10.2 mg/L
Titanium 7440-32-6	> 5000 mg/kg bw	-	-
Chromium 7440-47-3	> 3400 mg/kg bw	-	> 5.41 mg/L
Iron 7439-89-6	98,600 mg/kg bw	-	> 0.25 mg/L
Tungsten 7440-33-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Molybdenum 7439-98-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.10 mg/L
Niobium (Columbium) 7440-03-1	> 10,000 mg/kg bw	> 2000 mg/kg bw	-
Aluminum 7429-90-5	15,900 mg/kg bw	-	> 1 mg/L
Tantalum 7440-25-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.18 mg/L
Silicon 7440-21-3	> 5000 mg/kg bw	> 5000 mg/kg bw	> 2.08 mg/L
Cobalt 7440-48-4	550 mg/kg bw	>2000 mg/kg bw	<0.05 mg/L
Carbon 7440-44-0	> 2000 mg/kg bw	-	-

Boron 7440-42-8	> 2000 mg/kg bw	-	> 5.08 mg/L
Hafnium 7440-58-6	> 5000 mg/kg bw	-	>4.3mg/L

Information on toxicological effects

Symptoms May cause sensitization by skin contact. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Cobalt-containing powders may be harmful if inhaled.
Skin corrosion/irritation Product not classified.
Serious eye damage/eye irritation Product not classified.
Sensitization May cause sensitization by skin contact. Cobalt-containing alloys may cause sensitization by inhalation.
Germ cell mutagenicity Contains a suspected mutagen.
Carcinogenicity May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel 7440-02-0		Group 1 Group 2B	Known Reasonably Anticipated	X
Chromium 7440-47-3		Group 3		
Cobalt 7440-48-4	A3	Group 2A Group 2B	Known	X

Reproductive toxicity Contains a known or suspected reproductive toxin.
STOT - single exposure Product not classified.
STOT - repeated exposure Causes disorder and damage to the: Respiratory System.
Aspiration hazard Product not classified.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

This product as shipped is classified for aquatic chronic toxicity

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Nickel 7440-02-0	NOEC/EC10 values range from 12.3 µg/l for <i>Scenedesmus accuminatus</i> to 425 µg/l for <i>Pseudokirchneriella subcapitata</i> .	The 96h LC50s values range from 0.4 mg Ni/L for <i>Pimephales promelas</i> to 320 mg Ni/L for <i>Brachydanio rerio</i> .	The 30 min EC50 of nickel for activated sludge was 33 mg Ni/L.	The 48h LC50s values range from 0.013 mg Ni/L for <i>Ceriodaphnia dubia</i> to 4970 mg Ni/L for <i>Daphnia magna</i> .
Titanium 7440-32-6	The 72 h EC50 of titanium dioxide to <i>Pseudokirchnerella subcapitata</i> was 61 mg of TiO ₂ /L.	The 96 h LC50 of titanium dioxide to <i>Cyprinodon variegatus</i> was greater than 10,000 mg of TiO ₂ /L. The 96 h LC50 of titanium dioxide to <i>Pimephales promelas</i> was greater than 1,000 mg of TiO ₂ /L.	The 3 h EC50 of titanium dioxide for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of titanium dioxide to <i>Daphnia Magna</i> was greater than 1000 mg of TiO ₂ /L.
Chromium 7440-47-3	-	-	-	-
Iron 7439-89-6	-	The 96 h LC50 of 50% iron oxide black in water to <i>Danio rerio</i> was greater than 10,000 mg/L.	The 3 h EC50 of iron oxide for activated sludge was greater than 10,000 mg/L.	The 48 h EC50 of iron oxide to <i>Daphnia magna</i> was greater than 100 mg/L.
Tungsten 7440-33-7	The 72 h EC50 of sodium tungstate to <i>Pseudokirchnerella</i>	The 96 h LC50 of sodium tungstate to <i>Danio rerio</i> was greater than 106 mg of W/L.	The 30 min EC50 of sodium tungstate for activated sludge were greater than	The 48 h EC50 of sodium tungstate to <i>Daphnia magna</i> was greater than 96 mg of

	subcapitata was 31.0 mg of W/L.		1000 mg/L.	W/L.
Molybdenum 7439-98-7	The 72 h EC50 of sodium molybdate dihydrate to <i>Pseudokirchneriella subcapitata</i> was 362.9 mg of Mo/L.	The 96 h LC50 of sodium molybdate dihydrate to <i>Pimephales promelas</i> was 644.2 mg/L	The 3 h EC50 of molybdenum trioxide for activated sludge was 820 mg/L.	The 48 h LC50 of sodium molybdate dihydrate to <i>Ceriodaphnia dubia</i> was 1,015 mg/L. The 48 h LC50 of sodium molybdate dihydrate to <i>Daphnia magna</i> was greater than 1,727.8 mg/L.
Niobium (Columbium) 7440-03-1	-	-	-	-
Aluminum 7429-90-5	The 96-h EC50 values for reduction of biomass of <i>Pseudokirchneriella subcapitata</i> in AAP-Medium at pH 6, 7, and 8 were estimated as 20.1, 5.4, and 150.6 µg/L, respectively, for dissolved Al.	The 96 h LC50 of aluminum to <i>Oncorhynchus mykiss</i> was 7.4 mg of Al/L at pH 6.5 and 14.6 mg of Al/L at pH 7.5	-	The 48-hr LC50 for <i>Ceriodaphnia dubia</i> exposed to Aluminium chloride increased from 0.72 to greater than 99.6 mg/L with water hardness increasing from 25 to 200 mg/L.
Tantalum 7440-25-7	-	-	-	-
Silicon 7440-21-3	The 72 h EC50 of sodium metasilicate pentahydrate to <i>Pseudokirchnerella subcapitata</i> was greater than 250 mg/L.	-	-	-
Cobalt 7440-48-4	The 72 h EC50 of cobalt dichloride to <i>Pseudokirchneriella subcapitata</i> was 144 µg of Co/L.	The 96h LC50 of cobalt dichloride ranged from 1.5 mg Co/L for <i>Oncorhynchus mykiss</i> to 85 mg Co/L for <i>Danio rerio</i> .	The 3 h EC50 of cobalt dichloride for activated sludge was 120 mg of Co/L.	The 48 h LC50 of cobalt dichloride ranged from 0.61 mg Co/L for <i>Ceriodaphnia dubia</i> tested in soft, DOM-free water to >1800mg Co/L for <i>Tubifex tubifex</i> in very hard water.
Carbon 7440-44-0	The 72 h EL50 of Carbon to <i>Pseudokirchneriella subcapitata</i> was greater than 100 mg/L.	The 96 h LL50 of Carbon in water to <i>Danio rerio</i> was greater than 100 mg/L.	The 3 h EC50 of Carbon for activated sludge was 1000 mg/L.	The 48 h EL50 of Carbon to <i>Daphnia magna</i> was greater than 100 mg/L.
Boron 7440-42-8	The 72-h EC50 value for reduction of biomass of <i>Pseudokirchneriella subcapitata</i> exposed to Boric acid at pH 7.5 to 8.3 was 40.2 mg/L.	The 96-hr LC50 for <i>Pimephales promelas</i> exposed to Boric acid (82%)/borax (18%) mixture was 79.7 mg/L with water hardness of 91 mg/L and water pH of 8.0.	The 3 h NOEC of boric acid for activated sludge ranged from 17.5 to 20 mg/L.	The 48-hr LC50 for <i>Ceriodaphnia dubia</i> exposed to Boric acid/borax mixture ranged from 91 to 165 mg/L with pH ranging from 6.7 to 8.4.
Hafnium 7440-58-6	The 72 h EC50 of hafnium to <i>Pseudokirchneriella subcapitata</i> was greater than 8 µg of Hf/L (100% saturated solution).	The 96 h LC50 of Hafnium dioxide in water to <i>Danio rerio</i> was greater than the solubility limit of 0.007 mg Hf/L.	-	The 48 h EC50 of Hafnium dioxide to <i>Daphnia magna</i> was greater than the solubility limit of 0.007 mg Hf/L.

Persistence and degradability**Bioaccumulation****Other adverse effects****13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	RCRA - D Series Wastes
Chromium 7440-47-3	5.0 mg/L regulatory level

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT Regulated per 49 CFR, if quantity with particles smaller than 100 micrometers (0.004 inches) in an individual package equals or exceeds the reportable quantity (RQ) of 5000 pounds of chromium or 100 pounds of nickel

Proper shipping name UN/ID No. 3077 Environmentally hazardous substance, solid, n.o.s. (nickel alloy powder), RQ

Hazard Class 9

Packing Group III

Special Provisions 8, 146, 335, A112, B54, B120, IB8, IP3, N20, N91, T1, TP33

Emergency Response Guide Number Guide No. 171, Except for FIRE follow Guide No. 170

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL/NDSL Complies

EINECS/ELINCS Complies

ENCS Complies

IECSC Complies

KECL Complies

PICCS Not Listed

AICS Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Nickel - 7440-02-0	7440-02-0	49 - <100	0.1
Chromium - 7440-47-3	7440-47-3	0 - 32	1.0
Cobalt - 7440-48-4	7440-48-4	0.1 - <2.5	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes

Chronic Health Hazard Yes

Fire hazard No

Sudden release of pressure hazard No

Reactive Hazard

No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Nickel 7440-02-0		X	X	
Chromium 7440-47-3		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs
Nickel 7440-02-0	100 lb
Chromium 7440-47-3	5000 lb

US State Regulations

California Proposition 65

This product contains the Proposition 65 chemicals listed below. Proposition 65 warning label available at ATImetals.com.

Chemical Name	California Proposition 65
Nickel - 7440-02-0	Carcinogen
Cobalt - 7440-48-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Nickel 7440-02-0	X	X	X
Titanium 7440-32-6	X		
Chromium 7440-47-3	X	X	X
Tungsten 7440-33-7	X	X	X
Molybdenum 7439-98-7	X	X	X
Aluminum 7429-90-5	X	X	X
Tantalum 7440-25-7	X	X	X
Silicon 7440-21-3	X	X	X
Cobalt 7440-48-4	X	X	X
Hafnium 7440-58-6	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health hazards 1	Flammability 0	Instability 0	Physical and Chemical Properties - Personal protection X
HMIS	Health hazards 2*	Flammability 1	Physical hazards 0	

Chronic Hazard Star Legend

* = *Chronic Health Hazard*

Issue Date

09-Mar-2021

Revision Date

08-Apr-2021

Revision Note

New Safety Data Sheet

Note:

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Additional information available from:

Safety data sheets and labels available at ATImetals.com